

Material Safety Data Sheet

Copyright, 2013, MTI Corporation All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing MTI products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from MTI, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: MTI PTFE Condensed Liquid Binder for Li-ion Battery

MANUFACTURER: MTI

DIVISION: Energy and Advanced Materials Division

ADDRESS: MTI Corporation

860 South 19th Street, Richmond, CA 94804, USA

EMERGENCY PHONE: 1-888-525-3070 or (510) 525-3070

Issue Date: 01/29/13

Product Use:

Intended Use: PTFE

SECTION 2: INGREDIENTS

Ingredient	<u>C.A.S. No.</u>	<u>% bv Wt</u>
Polytetrafluoroethylene	NONE	54 - 62
Water	NONE	34 - 44
Polyoxyethylene monooctylphenyl Ether	NONE	2 - 5

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Emulsion

Odor, Color, Grade: White with slight ammonia odor.

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: May cause severe eye irritation. May cause target organ effects.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and

MATERIAL SAFETY DATA SHEET MTI EQ-Lib-PTFE 01/29/13

impaired vision.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Inhalation:

During heating:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Polymer Fume Fever: Sign/symptoms may include chest pain or tightness, shortness of breath, cough, malaise, muscle aches, increased heart rate, fever, chills, sweats, nausea and headache.

If thermal decomposition occurs:

May be harmful if inhaled.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention. **Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperatureNot ApplicableFlash PointNo flash pointFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not Applicable

5.2 EXTINGUISHING MEDIA

Non-combustible. Choose material suitable for surrounding fire.

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may be used to blanket the fire. Exposure to extreme heat can give rise to thermal decomposition. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air.

6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Observe precautions from other sections. Call MTI- HELPS line (1-888-525-3070) for more information on handling and managing the spill. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS. Seal the container.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid breathing of vapors, mists or spray. Avoid skin contact with hot material. Avoid eye contact with vapors, mists, or spray. For industrial or professional use only. Store work clothes separately from other clothing, food and tobacco products. No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to polymer fume fever caused by the formation of the hazardous decomposition products mentioned in the Reactivity Data section of this MSDS. Avoid skin contact. Do not breathe thermal decomposition products.

7.2 STORAGE

Keep container tightly closed. Store away from heat.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide local exhaust ventilation at transfer points. Use in an enclosed process area is recommended. Provide appropriate local exhaust when product is heated. For those situations where the fluid might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

MATERIAL SAFETY DATA SHEET MTI EQ-Lib-PTFE 01/29/13

8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Indirect Vented Goggles

•

8.2.2 Skin Protection

Avoid skin contact.

During processing or fabrication:

Avoid skin contact with hot material.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Neoprene

Nitrile Rubber

Polymer laminate

•

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

During heating:

Do not breathe vapors.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges and P100 particulate prefilters. Select and use respiratory protection to prevent an inhalation exposure based on the results of an exposure assessment. Consult with your respirator manufacturer for selection of appropriate types of respirators.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

Ingredient Polytotyofly operathylana	Authority	Type	Limit	Additional Information
Polytetrafluoroethylene	CMRG	TWA, as respirable	5 mg/m3	
		dust		
Polytetrafluoroethylene	CMRG	TWA, as total dust	10 mg/m3	

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form: Emulsion

Odor, Color, Grade: White with slight ammonia odor.

General Physical Form:

Autoignition temporature

Not An

Autoignition temperatureNot ApplicableFlash PointNo flash pointFlammable Limits(LEL)Not Applicable

MATERIAL SAFETY DATA SHEET MTI EQ-Lib-PTFE 01/29/13

Flammable Limits(UEL)

Boiling Point

100 °C

Density

1.2 - 1.6 g/ml

Vapor Density 25 [@ 20 °C] [*Ref Std*: AIR=1]

Vapor Pressure 18 mmHg [@ 20 °C]

Specific Gravity 1.2 - 1.6 [@ 23 °C] [*Ref Std:* WATER=1]

pH 9 - 10

Melting point Not Applicable

Solubility in Water Negligible [*Details*: Polymer not soluble]

Evaporation rate 1 [Ref Std: WATER=1]

Volatile Organic CompoundsNot ApplicableKow - Oct/Water partition coefNo Data Available

Percent volatile 45 %

VOC Less H2O & Exempt Solvents Not Applicable

Viscosity 10 - 20 MPa-s [@ 20 °C]

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

None known

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Condition Substance Tetrafluoroethylene At Elevated Temperatures Carbonyl Fluoride At Elevated Temperatures Carbon monoxide At Elevated Temperatures Carbon dioxide At Elevated Temperatures Hydrogen Fluoride At Elevated Temperatures Perfluoroisobutylene (PFIB) At Elevated Temperatures Toxic Vapor, Gas, Particulate At Elevated Temperatures

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility in the presence of a combustible material. Combustion products will include HF. Facility must be capable of handling halogenated materials. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

ID Number(s):

97-5000-1330-1, 97-5000-1342-6

For Transport Information, please visit www.mtixtl.com or call 1-888-525-3070 or (510) 525-3070.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact MTI for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

STATE REGULATIONS

Contact MTI for more information.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS. Contact MTI for more information.

INTERNATIONAL REGULATIONS

Contact MTI for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 3 Flammability: 0 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 1 Flammability: 0 Reactivity: 0 Protection: X - See PPE section.

Hazardous Material Identification System (HMIS®) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint and Coatings Association (NPCA).

Revision Changes:

Section 1: Product name was modified. Page Heading: Product name was modified. Section 5: Flash point information was modified. Section 9: Flash point information was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. MTI MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the MTI product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a MTI product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the MTI product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

MTI provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, MTI makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from MTI

MTI USA MSDSs are available at www.mtixtl.com